



Digital Velocity Decoder D-VD-2N-R

Ultrafast FPGA-based Digital Signal Processing

Optomet Vibrometers feature an end-to-end FPGA-based digital signal processing allowing a fully digital read-out of the measurement data. Digital signal processing avoids any drawbacks of analog demodulation which may result from component aging, temperature dependencies, noise and non-linearities. Significantly higher sensitivity, better resolution, and stability are the benefits of OptoMET's end-to-end digital signal processing. Extremely low noise levels produce precise results even from poorly reflecting measurement objects.



HIGHLIGHTS:

- Digital decoder
- 11 velocity measuring ranges
- Frequency range: 0 Hz - 25 kHz
- Max. velocity up to 5 m/s
- Resolution down to $1.7 \text{ nm s}^{-1}/\text{VHz}$
- Max. linearity error: 0.5 %

Remote Sense Velocity Decoder

All vibrometers series feature by default a velocity decoder and can be supplemented with a suitable displacement and/or acceleration decoder.

The D-VD-2N-R velocity decoder has been specially developed to register even the smallest mechanical vibrations and motions. It has 11 velocity measuring ranges from 2.45 mm/s to 5 m/s and is ultrasensitive in detecting tiny vibrations up to 1.7 nm/s.

Technical data

Pos.	Full Scale Output (Peak) m/s	Typical Resolution* $\mu\text{m s}^{-1} / \sqrt{\text{Hz}}$	Signal Frequency Range kHz	Max. Acceleration g
1	0.00245	0.0017	2.5	3.9
2	0.0049	0.002	5	15.6
3	0.01225	0.003	10	78
4	0.0245	0.012	25	392
5	0.049	0.018	25	784
6	0.1225	0.024	25	1,960
7	0.245	0.05	25	3,920
8	0.49	0.10	25	7,840
9	1.225	0.20	25	19,600
10	2.45	0.29	25	39,200
11	5	0.50	25	80,000

* The resolution is defined as the signal amplitude (rms) that produces 0 dB signal/noise ratio with 1 Hz spectral resolution at 50 % f_{max} .

